

## DATA SHEET FLH311

LAMPARA EXAMEN FLH-3, 35.000 LUX RODABLE CON FLEXO

Moveable examination lamp FLH-3 model, 35.000 lux with flex arm

CARACTERÍSTICAS TÉCNICAS		TECHNICAL CHARACTERISTICS
Fuente de luz	LED	Light Source
Temperatura de color	5000 °K	Colour temperature
CRI (Ra)	> 96	CRI (Ra)
Intensidad lumínica	1m - 35.000 lux 0,75m - 55.000 lux 0,5m - 65.000 lux	Luminous intensity
Vida media LEDs	60.000 h	Average LEDs Lifetime
Regulación de intensidad	25-100%	Brightness control
Diámetro campo a 1 m d <sub>50</sub>	Ø 100 mm	Light field diameter at 1m d <sub>50</sub>
Diámetro campo a 0,5 m d <sub>50</sub>	Ø 80 mm	Light field diameter at 0,5m d <sub>50</sub>
Diámetro campo a 1 m d <sub>10</sub>	Ø 170 mm	Light field diameter at 1m d <sub>10</sub>
Diámetro campo a 0,5 m d <sub>10</sub>	Ø 150 mm	Light field diameter at 0,5m d <sub>10</sub>
Profundidad de iluminación (L1 + L2) al 60%	95 cm	Depth of illumination (L1 + L2) at 60%
Voltaje	90-240 V	Voltage
	50-60 Hz	
Potencia	7 W	Power consumption
Número de LEDs	3	Number of LEDs
Montaje	Base rodable de 5 ruedas (2 con freno)* 5 castor stand (2 with brakes)*	Configuration
Peso	5,1 kg	Weight
Dimensión de embalaje	46 x 19 x 64 cm	Packing size
Normas aplicadas	EN60601-1, EN60601-2-41, EN60601-1-2, ISO 14971, ISO 13485, ISO 9001	Applied standards

\* Posibilidad de montar ruedas antiestáticas / Antistatic castors available

### DIMENSIONES / DIMENSIONS

