

## DATA SHEET IG-65M

LAMPARA DE RECONOCIMIENTO RODABLE SERIE IGLUX  
Moveable lamp of recognition IGLux series

| CARACTERÍSTICAS TÉCNICAS                  |  | TECHNICAL CHARACTERISTICS                  |
|---|--|--|
| Fuente de luz                             | <b>LED</b>   | Light Source                               |
| Temperatura de color                      | <b>4500 °K</b>   | Colour temperature                         |
| CRI (Ra)                                  | <b>&gt; 96</b>   | CRI (Ra)                                   |
| Intensidad lumínica                       | <b>1m - 65.000 lux</b>   | Luminous intensity                         |
| Vida media LEDs                           | <b>60.000 h</b>  | Average LED Lifetime                       |
| Regulación de intensidad                  | <b>20-100%</b>   | Brightness control                         |
| Diámetro campo a 1 m d <sub>50</sub>      | <b>Ø 130 mm</b>  | Light field diameter at 1m d <sub>50</sub> |
| Diámetro campo a 1 m d <sub>10</sub>      | <b>Ø 250 mm</b>  | Light field diameter at 1m d <sub>10</sub> |
| Profundidad de iluminación (L1+L2) al 60% | <b>85 cm</b>   | Depth of illumination (L1+L2) at 60%       |
| Voltaje                                   | <b>100-240 V<br/>47-63 Hz</b>  | Voltage                                    |
| Potencia                                  | <b>17 W / 42 VA</b>  | Power consumption                          |
| Número de LEDs                            | <b>12</b>  | Number of LEDS                             |
| Montaje                                   | <b>Base rodable de 4 ruedas (2 con freno)*<br/>4 castor stand (2 with brakes)*</b> | Configuration                              |
| Peso bruto / neto                         | <b>17kg / 15 kg</b>  | Gross / net weight                         |
| Dimensión de embalaje                     | <b>131 x 45 x 23 cm</b>  | Packing size                               |
| Normas aplicadas                          | <b>EN60601-1, EN60601-2-41, EN60601-1-2,<br/>ISO 14971, ISO 13485, ISO 9001</b>    | Applied standards                          |

\* Posibilidad de montar ruedas antiestáticas / Antistatic castors available

### DIMENSIONES / DIMENSIONS

